

Barcode scanner



SD-500

B W

Features

- Compact and slim size
- High scan rate
- Contact to middle reading range
- Long life and user friendly switch button
- Quick-release cable design for 3 in 1 interface
- Support GS1 DataBar (RSS code)

Specification

- **Depth of field:** 100mm@PCS90% 0.5mm
- **Width of field:** 50mm from window
- **Resolution:** 4mil/0.1mm@PCS90%
- **Ambient light:** 50,000 Lux Max.
- **Scan rate:** 200 scans/sec
- **Reading indicator:** Beeper and LED
- **Interface:** KBW/RS232/USB
- **Drop:** 40 inch(100cm) drop on Concrete Surface



SD-300

B W G

Features

- Advanced scanning performance
- Economical and durable and ergonomic design
- Easy to use and configure
- Complete data formatting and editing capabilities
- Reads most commonly used bar code symbologies
- Support GS1 DataBar (RSS code)

Specification

- **Depth of field:** 50mm@20mil/0.5mm, PCS90% (Contact type)
- **Width of field:** 80 mm
- **Resolution:** 4mil/0.1mm@PCS90%
- **Ambient light:** 5000 Lux Max.
- **Scan rate:** 100 scans/sec
- **Reading indicator:** Beeper and LED
- **Interface:** KBW/RS232/USB
- **Drop:** 40 inch (100cm) drop on Concrete Surface



SD-1000

B W

Features

- Advanced scanning performance
- Flexible communication
- Read status LED indicator and programmable beeper
- Quick-release cable design for 3 in 1 interface
- Support GS1 DataBar (RSS code)

Specification

- **Depth of field:** 100mm@20mil/0.5mm, PCS90%
- **Width of field:** 75mm
- **Resolution:** 4mil/0.1mm@PCS90%
- **Ambient light:** 5000 Lux Max.
- **Scan rate:** 75 scans/sec
- **Reading indicator:** Beeper and LED
- **Interface:** KBW/RS232/USB
- **Drop:** 40 inch(100cm) drop on Concrete Surface



SD-2000

B W

Features

- Advanced scanning performance
- Flexible communication
- Read status LED indicator and programmable beeper
- Quick-release cable design for 3 in 1 interface
- Support GS1 DataBar (RSS code)

Specification

- **Depth of field:** 50mm@20mil/0.5mm, PCS90% (Contact type)
- **Width of field:** 75mm
- **Resolution:** 4mil/0.1mm@PCS90%
- **Ambient light:** 5000 Lux Max.
- **Reading indicator:** Beeper and LED
- **Scan rate:** 75 scans/sec
- **Interface:** KBW/RS232/USB
- **Drop:** 40 inch(100cm) drop on Concrete Surface